

- **Multi Denomination De Le Rue Dispenser with Bunch delivery**
- **High Speed Thermal Receipt Printer with a Presenter**
- **12 mm Steel Chest meeting UL291 Level 1 specifications**
- **Kalignite NDC+ Network Interface protocol**
- **Audio & Video assist for New ATM users guidance**

Redicash III is high quality ATM European Design that works in any dust-free locations without air-conditioning with ambient not exceeding 40°C.

It dispenses up to four currency denominations.

EPP SS PIN Pad is mounted in a recessed area in the customer fascia for data security.

Redicash III fascia is in steel rather than plastic for higher security and has audio visual Assistance to guide & alert new ATM users for cash/card collection.

Redicash III follows current industry standards like XFS 3 and easily integrates into local or ATM networks using NDC+.

It can also work with a wireless link via CDMA or GPRS Cellular Network making it easily adaptable even in rural environment.

Redicash III offers the lowest cost of ownership and yet provides all advanced security features, such as encrypting PIN Pad (EPP) with triple DES security, the latest standard for PIN encryption.

Aplab's Redicash III is the cost effective ATM in the industry with every Feature of high cost foreign CDs.



Multimedia Interface	Technical Specifications	
Bright 15" TFT Colour LCD display Dip or motorized Hybrid card reader EMV 4.0 compliant smart card reader 16 key EPP and 8 Function keys. Audio/Video Assist for new customer Alert for Cash/Card collection.	DISPENSER De La Rue Friction Feed NMD100 with upto 4 Currency Denominations Bunch Delivery - 100 notes /bundle, Bunch retract Facility 3000 notes per cassette capacity.	NETWORK INTERFACE Kalignite NDC+ with XFS 3.0 Compliant.
Printer specifications	SECURITY	CONNECTIVITY RJ 45 Ethernet/Dial up Modem/ CDMA/GPRS.
RECEIPT PRINTER 80 mm Thermal printer with auto cutter and presenter.	Physical 12 mm UL291 Level 1 Safe Front Access.	PRODUCT DIMENSIONS 550 (W) x 1398 (H) x 700 (D) mm.
JOURNAL PRINTER 80 mm, 40 column dot matrix printer with take up spool.	Electronic Encrypting Pin Pad (EPP) with triple DES encryption. System : Pentium IV 2.6 GHz Windows 2000/XP.	POWER REQUIREMENT 150 - 280V AC 50Hz, 500VA (with UPS).
		WEIGHT : 500 Kg. Approx.