

- De La Rue Dispenser of field proven design
- High Speed Thermal Receipt Printer with a Presenter
- Kalignite NDC+ Network Interface protocol
- Audio and Video Assist for New ATM user guidance
- Field Proven in Rural Branches of major Indian Banks

Rupimat SD-CUBE is low cost single denomination ATM of European Design for working in a clean environment of a bank lobby or indoor third party location. It works in any dust free location even without air-conditioning at temperatures below 40°C

Rupimat ensures high degree of customer security, privacy and comfort in operation.

Rupimat features renowned De La Rue cash dispensing mechanism.

Customer interface is thru a Vandal proof SS PIN Pad mounted in a recessed area of the fascia.

The Rupimat fascia is in steel rather than plastic for security.

Rupimat has Audio Visual Assistance to guide and alert new ATM users for cash/card collection

Rupimat follows current industry standards like XFS 3 and easily integrates into local or ATM networks using NDC+. It can work with a wireless link via CDMA or GPRS Cellular Networks, making it easily adapted to virtually any environment.

Rupimat offers the lowest cost of ownership and yet provides all advanced security features, such as encrypting PIN Pad (EPP) with triple DES security; the latest standard for PIN encryption.

Aplab's Rupimat is the only low cost ATM in the industry with every feature of high cost foreign CDs.



Multimedia Interface	Technical Specifications	
<p>10.4" TFT Colour LCD Dip or motorized Hybrid card reader EMV 4.0 compliant smart card reader 16 key EPP and 8 Function keys. Audio/Video Assist for new customer Alert for Cash /Card collection.</p>	<p><b>DISPENSER</b> De La Rue Friction Feed Technology Single denomination Spray Dispenser Secure cash Cassette, Double note detection. 2000 Notes per Cassette Capacity.</p> <p><b>SECURITY</b></p> <p><b>Physical</b> 4 mm UL291 Business Hour Safe optional 12 mm safe.</p> <p><b>Electronic</b> Encrypting Pin Pad (EPP) with triple</p>	<p>SYSTEM : Pentium IV 2.6 GHz Windows 2000/XP.</p> <p><b>NETWORK INTERFACE</b> Kalignite NDC+ &amp; XFS 3.0 Compliant.</p> <p><b>CONNECTIVITY</b> RJ 45 Ethernet/Dial up Modem/ CDMA/ GPRS.</p> <p><b>PRODUCT DIMENSIONS</b> 550 (W) x 630 (H) x 700 (D) mm optional 800 mm high Pedestal.</p> <p><b>POWER REQUIREMENT</b> 150 - 280V AC 50Hz, 400VA (with UPS).</p> <p><b>WEIGHT : 95 kg Approx.</b></p>
<p><b>Printer specifications</b></p> <p><b>RECEIPT PRINTER</b> 80 mm Thermal printer with auto cutter and presenter.</p> <p><b>JOURNAL PRINTER</b> 80 mm, 40 column dot matrix printer with take up spool.</p>		