

Innovation. Delivered.

EASY PAY II

EasyPay II will not only serve your customers better but it will improve your customer service scores and ROI.

Easy Pay II increases revenue substantially by reducing transaction processing, reporting and documentation cost.

Self Service Bill Payment kiosk is also gaining ground, because it appeals to younger bill-payers who are more comfortable with convenience, technology and less comfortable with making payment at counters.

Easy Pay II is a unique solution for Bill payment :

- Convenience
- One Stop Access
- 24 X 7 Use
- Payment Through Cash, Cheque and Card
- Cheque Image on Receipt
- Instant Payment Through Credit/debit Card
- Low Cost
- Reads Bill with Barcode
- Modular Design
- Small Footprint

Easy Pay II enhances a company's customer service efforts, assist in reconciliation duties, serve as a remote office location and alleviate stress on in-house personnel collecting payments.

Best Engineering Design, security and latest Technology backed up with best service support are the core strengths of all Aplab's operations which Easy Pay II reflects.



Aplab
GLOBAL

SELF SERVICE BILL PAYMENT KIOSK

Technical Specifications :

Display	: 15" bright TFT LCD display.
Data Entry Options	: Touch Screen / Metal Keyboard (65 key) with track ball (IP 65).
System	: PIV or higher. Optional Thin client technology.
Network Interface	: ODBC / JDBC / XML over HTTPS.
Connectivity	: Ethernet LAN (TCP/IP).
Payment Options	:
Cash	: Cash acceptor (5, 10, 20, 50, 100, 1000 denominations), Deposit Box with separate lock & key, capacity to store 1000.
Cheque	: Front side high speed cheque scanner with MICR reader, 100 or 200 DPI image resolution with TIFF, JPEG or BMP image format. Cheque deposit box with separate lock & Key to store 500 cheques. Optional CTS enabled Cheque scanner.
Card	: DIP type Magnetic / Smart Card Reader.
Receipt Printer	: 3" (40 Column) high speed graphics thermal receipt printer with Auto cutter. Optional 112mm thermal printer / 80 mm dot matrix / A-4 thermal printer.
Barcode Reader	: Code 39 / code 128 / UPC / EAN and other standard codes.
Enclosure	: M.S. enclosure with powder coating. Colour options available.
Power Requirement	: 190 - 260 V AC, 50 Hz, (Wattage 750W).
Operating Environment	: +5°C to +40°C with 70% RH.
Dimensions	: 1400 (H) x 500 (W) x 480 (D).
Weight	: 80 Kg.



Aplab Banking & Retail Automation

APLAB LIMITED

Aplab House, A-5, Wagle Estate, Thane 400 604. India. Tel : 022-67395555, 25821861 Fax : 25823137
Email : kiosks@aplab.com Web : www.aplab.com / www.aplabbankingautomation.com